

# Rotowash - The Original

# The clever solution for sustainable efficiency in floorcare







High standard of floor hygiene achieved by the unique Rotowash cleaning action of twin cylindrical contra-rotating brushes for all types of hard floors and carpets.

Large floor cleaning capacity. Up to 90% savings on water and chemical costs.

**Quality Made in Austria** with reliable parts supply. Eco-friendly manufactured, recyclable.

# rotowa/h



Rotowash One machine for multiple applications





Rotowash Side Brush
Rotowash Rotocart
Rotowash Corner Brush



## Rotowash Plus

Featuring integrated electrical spraying unit with accurate water distribution on demand and precise spray jet ahead of the front brush.

A Universal safety handle for left and right hand operation

**B** Easy grip water release control

C Pivoting quick release cable holder

D 10m mains cable

E Removeable slim line clean water tank 7ltr

F See through water hose with snap on/off easy connection

H Waste water tray lid with water level indicator

J Electrical sprayer

M Brush pressure control knob

N Spring loaded clip for quick removal of handle

P Heavy duty side and front protector bumpers

R Easy to fit and remove brush axles

S Built-in brush location plate for simple and fast fitting of brushes

T Retractable transport rollers suspend load on brushes while not in operation

U Cylindrical brushes, easy to remove without using any tools. Available in multiple colours for hygiene control

- V Easily removable waste water tray
- W Safety thermal cut-out control
- X Specially coated aluminium body housing for high mechanical resistance
- Y Long life filter unit
- Z Self retractable spray jet nozzle





KJUD	K43D	KOOD	
550	950	1.150	Single-phase induction motor [Watt]
650	650	650	Brush speed [R.p.m]
300	440	600	Brush width [mm]
7	7	7	Clean water capacity [Litre]
2	2,5	3,5	Dirty water capacity [Litre]
** ***	electric spray	*** **	Water distribution
340	270	220	Brush pressure [g/cm <sup>2</sup> ]
24,5	32	35	Weight [kg]
366	366	366	Length [mm]
403	545	705	Width [mm]
205	205	205	Height w/o handle [mm]
** ***	1.000 - 205 variable	*** **	Height in operation [mm]
			Coverage
920	1.275	1.845	Hard floors [up to m²/h]
520	630	920	Soft floors [up to m <sup>2</sup> /h]

# Rotowash Classic

The standard models including loop handle, nonelectrical water dosage and distribution of the cleaning solution between the brushes.

- A Universal safety handle for left and right hand operation
- **B** Easy grip water release control
- C Pivoting quick release cable holder
- D 10m mains cable
- E Removeable slim line clean water tank 7ltr
- H Waste water tray lid with water level indicator
- I Clean water tray
- K Bowden controlled water distribution
- M Brush pressure control knob
- N Spring loaded clip for quick removal of handle
- O Ball valve controlled water flow
- P Heavy duty side and front protector bumpers
- R Easy to fit and remove brush axles
- S Built-in brush location plate for simple and fast fitting of brushes
- T Retractable transport rollers suspend load on brushes while not in operation
- U Cylindrical brushes, easy to remove without using any tools. Available in multiple colours for hygiene control
- V Easily removable waste water tray
- W Safety thermal cut-out control
- X Specially coated aluminium body housing for high mechanical resistance





<b>R30A</b> /	R305	R45A	/ R45S	<b>R60A</b>	RAOS
NJUN	NJUJ	NTJA	11433	KOUA I	NOOS


550	950	1.150	Single-phase induction motor [Watt]
650	650	650	Brush speed [R.p.m]
300	440	600	Brush width [mm]
1,5 / 7	2/7	3 / 7	Clean water capacity [Litre]
2	2,5	3,5	Dirty water capacity [Litre]
gravity	gravity	gravity	Water distribution
325	260	210	Brush pressure [g/cm <sup>2</sup> ]
22,5 / 23,5	30 / 31	33 / 34	Weight [kg]
366	366	366	Length [mm]
403	545	705	Width [mm]
205	205	205	Height w/o handle [mm]
** *** 1.000 - 205 variable *** **			Height in operation [mm]
			Coverage
430	720	890	Hard floors [up to m <sup>2</sup> /h]
170	270	430	Soft floors [up to m <sup>2</sup> /h]

## Rotowash Flex

The stick handle enhances flexible working in tight areas. An optional tank is available.

- A Handle for left and right hand operation switches motor by tilting
- **B** Easy grip water release control
- C Pivoting quick release cable holder
- D 10m mains cable
- G Anodized aluminium handle, easy to stow
- H Waste water tray lid with water level indicator
- I Clean water tray
- K Bowden controlled water distribution
- L Coupling disconnects handle
- M Brush pressure control knob
- P Heavy duty
- side and front protector bumpers
- R Easy to fit and remove **brush axles**
- S Built-in brush location plate for simple and fast fitting of brushes
- T Retractable transport rollers suspend load on brushes while not in operation
- U Cylindrical brushes, easy to remove without using any tools.
   Available in multiple colours for hygiene control
- V Easily removable waste water tray
- W Safety thermal cut-out control
- X Specially coated aluminium body housing for high mechanical resistance





230

100

375

150

400	550	950	Single-phase induction motor [Watt]
650	650	650	Brush speed [R.p.m]
200	300	440	Brush width [mm]
1/3	1,5 / 3	2/3	Clean water capacity [Litre]
1,5	2	2,5	Dirty water capacity [Litre]
gravity	gravity	gravity	Water distribution
280	300	260	Brush pressure [g/cm <sup>2</sup> ]
15 / 16	20,5 / 21,5	27,5 / 28,5	Weight [kg]
366	366	366	Length [mm]
303	403	545	Width [mm]
205	205	205	Height w/o handle [mm]
** ***	1.000 - 205 variable	*** **	Height in operation [mm]

650 220 Coverage

Hard floors [up to m<sup>2</sup>/h]

Soft floors [up to m<sup>2</sup>/h]

### Rotowash Escalator



# Escalating to new heights ... and getting into the grooves!

The Rotowash specialist machine model R45B Escalator achieves a high quality deep clean on escalators treads and travelators.

In one pass the R45B Escalator washes, scrubs, collects the soil, retrieves the water immediately, and dries.

Additionally, in a matter of seconds the R45B Escalator can be switched to standard floor cleaning mode.



R45B ESC

The Side Brush comes as a standard on the R45B ESC.

950	Single-phase induction motor [Watt]
650	Brush speed [R.p.m]

440 Brush width [mm]
7 Clean water capacity [Litre]

2,5 Dirty water capacity [Litre] electric spray Water distribution

270 Brush pressure [g/cm²]

32 Weight [kg]
366 Length [mm]
545 Width [mm]

205 Height w/o handle [mm]
1.000 - 205 variabel Height in operation [mm]

Coverage

1.275 Hard floors [up to m²/h]
630 Soft floors [up to m²/h]

#### ard ing bing

#### brush range

# Vinyl/Lino Terrazzo/Marble Concrete/Stone Profiled Rubber Tiles Safety Floors Resin Floors Wooden Floors Sports Floors Vinyl/Lino Terrazzo/Marble **Rubber Floors** Wood Floors Oiled Woodfloors Industrial Commercial **Domestics** Metal Floors **Entrance Matting**

## Rotowash

# The factory

**Rotowash** is amongst the pioneers in the design and manufacture of compact scrubberdryer floorcleaning machines specialized in twin cylindrical counter rotating brush technology.

Rotowash floorcleaning machines are being successfully employed internationally for more than 38 years. Rotowash machines are designed and made in Austria using components of the highest quality. The management and production systems undergo frequent audits by British Standard Institute – BSI – according to ISO 9001. Rotowash products are frequently audited and approved by OVE, Austria and BSI and conform to the high standards of design, quality and safety set by CE – Conformity European.

Our experience and expertise developed over the past four decades as a major manufacturer and supplier, enables us to be the catalyst to help you identify and assess your floor maintenance needs.



Rotowash Reinigungsmaschinenfabrik GmbH Austria, 8435 Wagna, Karl-Fink-Park 1 T+43 3452 76611-0 F+43 3452 76611-52 www.rotowash.at office@rotowash.at